

Water Treatment

PR10-SWRO

PR Water Treatment Sea Water Reverse Osmosis Membrane

PR PROJECT RENTALS

Sales and Rental Solutions

System Features

- SWRO PR Water-Flo membrane cartridge (4 cartridges)
- Electrical control panel with PLC and DOL Pumps
- Feed and high pressure pumps
- 2x PR Water-Flo membrane pre-treatment and 2x guard filters
- Control valve
- Pressure gauges, flow meters
- Permeate conductivity meter
- System on racking, PVC and stainless steel piping
- C.I.P. setup with tank

Technical Data

PR Water Treatment Sea Water Reverse Osmosis Membrane

Configuration	Spiral-wound, FRP wrapping
Type	TFC (Thin Film Composite)
Material	PA (Polyamide)
Membrane Size	Diameter 4"x Length 40"
Effective Area	74 sq ft/membrane
Recovery	35-45%
Operating Temperature	<50° C
Operating Pressure	<70 Bar
Flow Rate	Single Membrane 0.1 m ³ /h
Flow Capacity	2.4m ³ /day
Feed Max. Turbidity	< 1.0 NTU *
pH Range	3-10
Chlorine Concentration	<0.1pm
Electrical Power	415v, 50Hz, Three Phase
Dimensions	1.77m(H)x 1.15m(L)x 0.65m(W)
Weight	250kg



- ✓ Fully automated
- ✓ Easy operation and maintenance
- ✓ Use as a stand alone system or in conjunction with the PR Water Clarification units
- ✓ NO chemicals required for solids separation

Contact Project Rentals today for your water solution requirements

t. 1300 399 499

e. sales@projectrentals.com | w. www.projectrentals.com

PR PROJECT RENTALS
Power and Reliability